



- Can be used for handling seed, fertilizer, chemicals, and other products on pallets. Can also be used to handle large round bales.
- · Fits Cat. II or III three point hitch tractors.
- · Can also fit Cat II or III quick hitches.
- · Solid high tensile steel teeth are adjustable from 20" 48".
- · Heavy duty greaseable rollers provide smooth operation.
- Attaches to tractor very easily and when removed stands by itself and requires minimum storage space.
- Optional Backguard prevents product from shifting towards tractor. (TFL-2501)
- Optional ends are available to convert a standard 4" x 8" cylinder for use as top link when tilting is required. (No need to buy a complete new cylinder.)
- · Maximum Lift Capacity is 4000 pounds.
- Maximum lift height is 70" or 94" with 3 pt. in fully raised position. (Will vary with tractor.)
- · Fork size 1 1/2" x 4" x 46" solid steel rated at 2400# pounds each.
- 2 1/2" x 42" or 66" Stroke Cylinder, single or double acting. (No hoses provided.)
- Completely assembled other than teeth to be mounted with approximate shipping weight of 660 pounds.

3 POINT MOUNTED FORKLIFT



Tebben Pic-Rite™ rock picking bucket attachment digs rocks or skims under the surface for smaller rocks. Operates mechanically (no hydraulics needed) flips rocks into bucket by simply backing up.



Tebben tractor loader fork assembly with universal mounting brackets.



Tebben Skid Steer mount fork attachment with universal mount plate.



Optional Top Link Cylinder (Category 2)

